

Resilient Wedge Gate Valve - C515

Kennedy Valve AWWA C515 Resilient Wedge Gate Valves meet or exceed the requirements of AWWA standard C515, UL-262/FM-1120/1130, ULC - Underwriters' of Canada, and NSF Certified.

Available in either non-rising stem (NRS) or outside screw & yoke (OS&Y). NRS style is available with post plate for adaptation with an indicator post.

Accessories

- KVOS OS&Y Monitor Switch
- Indicator Posts
- "T" Handles
- Stem Guides
- 2" Sq. Operating Nuts
- Floorstands (NRS)
- Handwheels
- Extension Stems
- Chain Wheels

Working Pressure

UL/FM 200 PSI. (2"-24")

Hydrostatic Test Pressure

Shell, 500 PSI. (2"-24")

Seat Test Pressure

Seat, 250 & 400 PSI. (2"-24")



C515 2"-12" END CONNECTIONS & SIZE RANGE

KS-Reduced Wall 200 PSI

END CONNECTION	NRS
FLG	2" - 12"
MJ x MJ	2", 3" - 12"
MJ x FLG	3" - 12"
MJ x FLG Tap	4" - 12"
Cutting-In	4" - 12"
Tyton x Tyton	4" - 12"
Tyton x FLG	4" - 12"
FLG x GRV	2.5" - 10"
GRV x GRV	2.5" - 10"
PVC with Gaskets	2" - 8"
Threaded	2" - 3"

* 3" - 12" NRS Available with Post Indicator Plates

KS-Reduced Wall 200 PSI

END CONNECTION	OS&Y
FLG	2.5" - 12"
FLG x GRV	2.5" - 10"
GRV x GRV	2.5" - 10"

C515 14"-24" END CONNECTIONS & SIZE RANGE

KS-Reduced Wall 200 / 250 PSI

END CONNECTION	NRS	PSI
FLG	14" - 16"	250
MJ x MJ	14" - 16"	250
MJ x FLG	14" - 16"	250
MJ x FLG Tap	14" - 16"	250
Tyton x Tyton	14" - 16"	250
FLG	18" - 24"	200
MJ x MJ	18" - 24"	200
MJ x FLG	18" - 24"	200
MJ x FLG Tap	18" - 24"	200
Tyton x Tyton	18" & 20"	200

* 14" - 24" NRS Available with Post Indicator Plates

KS-Reduced Wall 200 / 250 PSI

END CONNECTION	OS&Y	PSI
FLG	14" - 16"	250
FLG	18" - 24"	200

KVOS-OS&Y Monitor Switch optional; switch not sold separately.